

Solis

90 HP

MORE POWER
MORE SAVINGS



A Product Of

SONALIKA
INTERNATIONAL

SOLIS



STANDARD FEATURES



Engine

Engine Type	4105 ELT with coldstart
HP Category	90
No. of Cylinders	4
Aspiration	Turbo Charged & Intercooler
Bore/Stroke(mm)	105/118
Cubic Capacity (cc)	4087
Rated RPM (+/-25mm)	2200
Air cleaner	Dry Air Cleaner with Clogging Sensor.
Max Torque (Nm) @ RPM	339(+/-5%) @ 1400 RPM(+/-100)



Transmission

Drive	2wd/4wd
Clutch	Double Clutch
Gearbox	12F+12R
Transmission	Synchromesh

Speed (Forward)

Maximum (Speed Km/Hr)	32.31 @ 2200
Minimum (Speed Km/Hr)	1.57 @ 2200

Brakes

Brakes	Oil immersed brakes
Type of actuation	Mechanical
Parking Brake	Yes, Independnet (Hand operated)

Differential lock

Differential lock	Yes, Foot Operated
-------------------	--------------------



PTO

PTO (rpm)	540,540E with independent PTO.
PTO (actuation)	Mechanical, Hand operated

Steering

Steering	Power Steering
----------	----------------

Electrical

Battery	12V, 110Ah
Alternator	12V,36Amp
Seven pin trailer socket	Yes

Hydraulics

Position Control	To hold Lower links at any desired height
Automatic Draft Control	Maintain uniform draft
3 point linkage	CAT2
Lifting Capacity	2500 kg
Auxiliary Hydraulic Circuit	2DA/2SA
No. of Spool Valves	4

Safety Switch

Clutch Safety Switch	Yes
PTO Safety Switch	Yes
Neutral Safety Switch	Yes

Capacity (Itrs)(+/-5%) approx.

Fuel tank (Lit)	76
Eng Oil (Lit)	10.75
Hyd+Tran (Lit)	37.35

Turning Diameter meter

Turning diameter With Brakes (m)	8.12 m (R) /8.31m(L)/9.12 m (R)/ 9.37 m (L)
Turning diameter Without Brakes (m)	10.24 m (R) /10.47 m(L) /12.78m (R)- 13.10 (L)

Tyre

Front	9-16/12.4-24
Rear	18.4-30

Dimension & Weight(+/-5%)

Weight(kg)	2870/3150(Unballasted)
Wheel Base (mm)	2240/2350
Total Length (mm)	3925/3980
Total Width (mm)	2000(min)-2400(max)
Height (mm)	2640(ROPS)
Min Ground Clearance (mm) min	405
Front Track (mm)	1420-1650/1495-1835
Rear Track (mm)	1500-1900

Others

Fuel Indicator gauge	Yes
Registration Plate with light	Yes,with E-marked light
Front Toe Hook	Yes
ROPS	Yes
Driver seat	Yes,(E-marked) driver seat
Front & rear weights	Front 72 Kg base weight +6X31 Kg removable weights and rear 1X34 Kg at each wheel.
Trailer hitch	Rear Rotating toe hook
Drawbar	Swinging draw bar with Linkage crossbarYes
Canopy	



* Images are for Illustration purpose.

* Technical Specification can be changed for enhancement of the product.

Dealer Stamp



International Tractors Limited

H.O: Plot No. 29 and 31, Aggarwal Mall, CBD Ground, Near Karkardooma Court, Delhi-110032 (India). Phone: +91 11 22600700, Fax: +91 11 22377472

Works: Jalandhar Road, Hoshiarpur-146022, Punjab (India). Phone: +91 1882 302220, 302221, Fax: +91 1882 302293, E-mail: exports@sonalika.com , Website: www.sonalika.com.

www.facebook.com/SonalikaTractor | www.twitter.com/SonalikaTractor | www.linkedin.com/groups/Sonalika-Tractor

NON EEC