

SOILS

110 HP

MORE POWER
MORE SAVINGS



A Product Of

SONALIKA
INTERNATIONAL

SOLIS



STANDARD FEATURES



Engine	Engine Type HP Category No. of Cylinders Aspiration Cubic Capacity (cc) Rated RPM (+/-25mm) Air cleaner Cold Star Max Torque @ RPM (Nm) Exhaust	4105VLT Turbocharged water Cooled Engine 110 4 Turbo Charged 4087.054963 2200 Compact Dry - two paper elements and aspirator or 2-stage air cleaner with a highly efficient cyclone block. Yes 420@1300 Vertical Updraft
Transmission	Drive Clutch Gearbox Front Axle Transmission	4WD Double Clutch Cararo-24F+24R with Mechanical Shuttle Carraro make Syncromesh
Speed (Forward)	Maximum (Speed Km/Hr) Minimum (Speed Km/Hr)	36.58 0.57
Brakes	Brakes Type of actuation Trailer Brake Hand brake	Hydraulic Assisted Wet disc brakes operated by two foot pedals that can be locked together. Mechanical Hydraulic Trailer braking Independent
Differential lock	Differential lock	Switch Operated
PTO	PTO (rpm) PTO (actuation)	540/540E Mechanical
Steering	Steering	Power Steering
Electrical	Battery Alternator Seven pin trailer socket	12V, 110 AH 90 AH Yes
Hydraulics	3 point linkage Stay Bars Hydraulic lifting capacity Auxiliary hydraulic circuit EHR Lift rods	Cat. 2: Self Locking type with stay bar + ladder assembly Yes, adjustable 4500 Kg 2 DA/2SA DCV + 1 DA DCV with Detent and Float Position Control, Draft Control, Traditional Draft Control, Auto Draft Control Yes, adjustable
Safety Switch	Clutch Safety Switch PTO Safety Switch Neutral Safety Switch	Yes, adjustable Yes Yes
Capacity (ltrs)(+/-5%) approx.	Fuel tank (Lit)	115
Turning Diameter	Turning diameter with Brakes (m) Turning diameter without Brakes (m)	10.4 11.4
Tyre	Front Rear	380/85R24 460/85R34
Dimension & Weight(+/-5%)	Weight(kg) Wheel Base (mm) Total Length (mm) Total Width (mm) Height (mm) Min Ground Clearance (mm) Front Track (mm) Rear Track (mm)	4250 Kg with standard Ballast 2376 4045 2225 2816 488 mm at front axle 1615 - 2000 1724 - 1890
Others	Fuel Indicator gauge Front Toe Hook Front & Rear weights with std. Ballast Trailer hitch ROPS FOPS	Yes Yes with removable weights Front : 72 Kg Base weight + 31kg X8 overhanging Weight, Rear: 40kg on each wheel Quick Attach TPL and Automatic/Semi-automatic clevis hitch with ladder assembly & piton Yes Yes Optional
Optional Features	Optional Tyres	Front-380/70R24, Rear-480/70R34

Dealer Stamp



International Tractors Limited

H.O: Plot No. 29 and 31, Aggarwal Mall, CBD Ground, Near Karkardooma Court,
 Behind Hotel Kempinski, Delhi-110032 (India). Phone: +91 11 22600700, Fax: +91 11 22377472
 Works: Jalandhar Road, Hoshiarpur-146022, Punjab (India). Phone: +91 1882 302220, 302221,
 Fax: +91 1882 302293, E-mail: exports@sonalika.com, Website: www.sonalika.com.

www.facebook.com/SonalikaTractor |
 www.twitter.com/SonalikaTractor |
 www.linkedin.com/groups/Sonalika-Tractor